



Compatible with **HI VALUE** App

VRM-2SN

Digital Manifold Gauge II **NEW**

Touch. Read. Master. Introducing VRM-2SN, the next-generation manifold gauge built to elevate your workflow.

The VRM-2SN is the ultimate manifold gauge every HVAC technician needs. With a true plug-and-play setup, simply hook up your hoses once and handle it all: diagnostics, charging, and evacuation — seamlessly in one device.

What truly sets VRM-2SN apart is its user-first design. Visualization isn't just about looks — it's about streamlining workflows. Inspired by aviation-grade UI principles, the HD color touchscreen and enhanced interface make all three key functions more intuitive, visual, and precise: Manifold Gauge Mode, Leak Test Mode, and Evacuation Mode with decay test. And because usability goes hand in hand with personalization, VRM-2SN offers four themes, including Daylight Mode for clear visibility under direct sun, and expect even more options with upcoming firmware updates.

This isn't just a gauge that gets the job done. It's a gauge that makes the job better.

VALUE Classic Theme



Stellar Theme



Boost Theme



Daylight Theme



VRM-2SN

Digital Manifold Gauge II

NEW



Touch • Read • Master

Precision, Smart and Wireless

- Class 0.4 accuracy with digital display
- Bluetooth connections with temp clamps & micron gauge
- Work with HiVALUE App
- Supports over 100 refrigerants, updatable via App

Multiple Operation Modes

- Manifold Gauge mode with SH/SC display
- Leak Test mode
- Evacuation mode with decay test function
- Touchscreen navigation for faster operation

Powerful Visual w/ HD Color Interface

- Choose your work style from 4 themes: Classic, Stellar, Boost, Daylight
- Convert data into visuals with enhanced UI
- Self-explanatory interface
- Highly responsive 5.5" touch screen



VRM-2SNXV Packaging



Model	VRM-2SN	VRM-2SX	VRM-2SNXV
Refrigerant Type	R-11, R-12, R-13, R-22, R-23, R-32, R-113, R-114, R-115, R-116, R-123, R-124, R-125, R134A, R-236fa, R-245fa, R-290, R401A, R-401B, R-402A, R-402B, R-403B, R-404A, R-406A, R-407A, R-407B, R-407C, R-408A, R-409A, R-410A, R-413A, R-414A, R-414B, R-416A, R-417A, R-417C, R-420A, R-421A, R-421B, R-422A, R-422B, R-422C, R-422D, R-424A, R-427A, R-428A, R434A, R-437A, R-438A, R-448A, R-449A, R-450A, R-452A, R-452B, R-453A, R-454B, R-454C, R-458A, R-500, R-501, R-502, R-503, R507A, R-508B, R-513A, R-600, R-600a, R-601, R-601a, R-1233zd, R-1234yf, R-1234ze OTA upgradable, supports 100 common refrigerants		
Pressure Range	-29.9 inHg to 725 psi		
Bluetooth Range	80 m line of sight		
Power Supply	Rechargeable Li-ion Battery		
Accessory	/	VMT-1S (Low Side), VMT-2S (High Side), Charging Cable, VXS-301 Box	VMV1S, VMT-1S (Low Side), VMT-2S (High Side), Charging Cable, VXS-301 Box